

JSB-PTZ22X / JSB-PTZ22XIN

PTZ Cameras



1/4" Sony CCD



480 TV Lines



4mm~88mm

Lens Furnished



AC 24V

Power Supply



Advanced Zoom&Pan PTZ Camera with 360° Pan Rotation

Product Features

- Color Camera with Sony 1/3" CCD Sensor
- 5" Compact, Low Profile Color Dome Camera
- 360° Continuous Pan Rotation
- Continuous Auto Focus
- Variable Speed 0.2 – 15rad/s
- Auto Turn Around Function
- 64 Presets
- Home Position
- Pan/Tilt Speed Proportional to Zoom Ratio
- Minimum illumination: 0.07 Lux
- Advanced DSP Camera
 - Auto White Balance
 - Backlight Compensation
 - Auto Iris Control
 - Electronic Shutter
- Remote Control via RS-485
- On Screen Display for Camera Control
- Built in 4 Alarm Inputs



JSB-PTZ22XIN

Product Specification

Model No.	JSB-PTZ22X / JSB-PTZ22XIN	
Zoom Ratio	22X optical 10X digital	
Effective Pixels	NTSC: 542H x 496V	PAL: 542H x 586V
Sensor Type	1/4" color CCD	
Scanning System	NTSC: 525lines, 60fields/sec	PAL: 625lines, 50fields/sec
Video Output	1.0Vpp / 75Ω, BNC	
Horizontal Resolution	480 TVL	
S/N Ratio	More than 48db	
Sensitivity	0.07~2.5 Lux (F1.6)	
Focal Length	4~88 mm	
Focus Mode	Auto / Manual	
White Balance	Auto / Manual	
Iris Control	Auto / Manual	
Electronic Shutter	1/60~1/120k sec. (NTSC)	1/50~1/120k sec. (PAL)
AGC Control	Auto / Manual	
BLC	ON/OFF	
Pan Range	0~360° speed 0~15°/s (Fixed 15rad/s for constant dome)	
Tilt Range	0~90° speed 0~15°/s (Fixed 15rad/s for constant dome)	
Preset	64 presets (max)	
Auto Cruise	At best 6 cruises	
Power Supply	AC 24V ± 10% 1.75A	
Power Consumption	30VA (including the fan/heater device)	
Weight	8.81 lb. (4kg)	